

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A key pad assembly comprising:
a top cover placed over a stack of keypad components;
a bottom cover placed under the stack; the top cover and the bottom cover defining a common perimeter; and
an over molded portion that extends around the perimeter ~~[[over molded around the stack]]~~ to form a self contained key pad unit~~[[; and~~
~~an identification component that automatically identifies the key pad to a device that hosts the self contained key pad unit]]~~.
2. (Previously Presented) The key pad assembly of claim 1, the top cover and the bottom cover sandwich the stack.
3. (Original) The key pad assembly of claim 1, the top cover and the bottom cover are over molded to create a sealed common boundary.
4. (Original) The key pad assembly of claim 1, the stack comprises a printed circuit board with a flex member, an electro luminous panel, a silicone membrane with a plurality of keys, placed on top of each other.
5. (Original) The key pad assembly of claim 3, the flex member provides an electrical connection between the self contained key pad unit and a device that hosts the self contained key pad unit.
6. (Cancelled)
7. (Original) The key pad assembly of claim 5, the flex member protrudes out a trough of the self contained key pad unit.

8. (Previously Presented) The key pad assembly of claim 1, the bottom cover with a recess that houses a speaker therein.
9. (Previously Presented) The key pad assembly of claim 1, the top cover and bottom cover fabricated from at least one of polycarbonates, thermoset plastics, or thermoformed plastic.
10. (Original) The key pad assembly of claim 1, an illumination color or a brightness on a surface of the keypad indicates a mode of the key pad.
11. (Currently amended) A method of fabricating a self contained key pad comprising:
sandwiching a plurality of key pad components between a top cover and a bottom cover, the top cover and bottom cover defining a common perimeter; and
inserting molding around the ~~[[key pad components]]~~perimeter for ~~[[an encapsulation]]~~
encapsulating ~~[[thereof between]]~~ the top cover and the bottom cover~~[[; and~~
~~— automatically identifying the self contained key pad to a host unit upon mounting thereon by an identification tag]].~~
12. (Original) The method of claim 11 further comprising sandwiching the key pad components between the top and bottom cover.
13. (Original) The method of claim 11 further comprising housing a speaker in a recess of the bottom cover.
14. (Original) The method of claim 11 further comprising providing electrical connections to a host unit *via* a flex member.
15. (Cancelled)

16. (Currently amended) A self contained key pad comprising:
a stack comprising:
a membrane with a plurality of keys placed thereupon,
a printed circuit board positioned beneath the membrane;
a top cover placed over the stack; and
a bottom cover placed under the stack, the top cover and the bottom cover define a common boundary around the stack, the common boundary over molded to encapsulate the stack between the bottom cover and the top cover~~[[; and~~
~~——an identification tag that automatically identifies the key pad to a device that hosts the self contained key pad unit]]~~.
17. (Original) The self contained key pad of claim 16, the common boundary includes a contact surface of the top and bottom cover.
18. (Original) The self contained key pad of claim 18, the common boundary includes a perimeter common to the top and bottom cover.
19. (Original) The self contained key pad of claim 18, the bottom cover connected to a piezo electric speaker.
20. (Original) The self contained key pad of claim 18, the bottom cover contacts the printed circuit board.
21. (Original) The self contained key pad of claim 18, the top cover and the bottom cover sandwich the stack.
22. (Cancelled)
23. (Previously Presented) The key pad assembly of claim 1 further comprising an identification component that automatically identifies the key pad to a device that hosts the self contained key pad assembly.

24. (Previously Presented) The self contained key pad of claim 16 further comprising an identification component that automatically identifies the self contained key pad to a device that hosts the self contained key pad.